

## SUPEREX FR FR PVC Insulated Single Core Cables



RR Kabel make Single Core unsheathed flexible bright Electrolytic annealed multistrand bare copper conductor, FR PVC Insulated Industrial Cables for working voltages upto and including 1100 Volts, as per IS 694 : 2010 (HSN CODE : 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
0.75	24/0.2	824	24
1.0	14/0.3	1117	20
1.5	22/0.3	1638	12
2.5	36/0.3	2616	12
4.0	56/0.3	3802	8
6.0	84/0.3	5666	4
10.0	140/0.3	10422	3
16.0	126/0.4	16737	2

## UNILAY HR FR HR FR PVC Insulated Single Core Cables



RR Kabel make Single Core unsheathed flexible bright Electrolytic annealed multistrand bare copper conductor, HR FR PVC Insulated Industrial Cables for working voltages upto and including 1100 Volts, as per IS 694 : 2010 (HSN CODE : 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
1.0	37/0.19	1180	20
1.5	37/0.23	1720	12
2.5	61/0.23	2754	12
4.0	61/0.29	4182	8
6.0	91/0.29	6218	8

## FLAMEX FR-LSH FR-LSH PVC Insulated Single Core Cables



RR Kabel make Single Core unsheathed flexible bright Electrolytic annealed multistrand bare copper conductor, FR-LSH PVC Insulated Industrial Cables for working voltages upto and including 1100 Volts, as per IS 694 : 2010 (HSN CODE : 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
1.0	14/0.3	1169	20
1.5	22/0.3	1721	12
2.5	36/0.3	2742	12
4.0	56/0.3	3985	8
6.0	84/0.3	5918	4

Note: As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guidelines and are as per market convention, It may vary within the prescribed limit of IS:8130-2013, with related classes and tables.