

BRAIDED CABLES



Flexible / Stranded Bare Copper Conductor, PVC Insulated, Annealed Tinned Copper Braided with Optimum coverage and Outer PVC sheathed Industrial Braided cables, Voltage Grade 300/500V.

Size in Sq.mm / Rate Per 100 Meter (in INR)						
SIZE	0.25	0.50	0.75	1.00	1.50	2.50
2 Core	4959	5768	6141	6950	8864	12369
3 Core	5336	6191	7629	8444	11239	16397
4 Core	6416	7869	9357	10689	13650	21429
5 Core	8035	8595	10882	12618	16683	25150
6 Core	9466	9585	11972	14744	19294	-
7 Core	9994	10306	13936	16273	20749	32771
8 Core	10709	11624	14868	18187	23969	-
9 Core	-	-	-	-	26555	-
10 Core	12793	14768	18531	22501	30085	-
12 Core	14174	16062	21255	26853	35393	53208
14 Core	-	18399	24256	30483	41062	-
16 Core	-	20712	27346	34312	45326	-
18 Core	19950	22750	30358	38017	50398	-

Size in Sq.mm / Rate Per 100 Meter (in INR)				
SIZE	4.0	6.0	10.0	16.0
2 Core	18730	25811	-	-
3 Core	25712	35765	-	-
4 Core	31161	43905	75112	123870

Note : Minimum Order Quantity (MOQ)

Size - upto 0.25 x 8C - 5 KM, upto 0.25 x 8C to 18C and 0.50 to 1.50 x 7C - 3 KM,
 0.50 x 8C to 4.0 x 4C - 2 KM, 0.50 x 22C to 1.00 x 27C - 2 KM.