

FIREX LSOH LOW SMOKE ZERO HALOGEN 90°C.



RR Kabel make Single Core unsheathed Electrolytic annealed multistrand bare copper conductor Low Smoke Zero Halogen (LSOH) Insulated Industrial Cables in Voltage grade upto and including 1100 Volts. (HSN Code : 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
1.00	14/0.3	1401	20
1.50	22/0.3	2000	12
2.50	36/0.3	3160	12
4.00	56/0.3	4707	8
6.00	84/0.3	6818	4

* LSOH - Conductor Conforming to IEC 60228 & Insulation Conforming to EN 60332-1-2 & 3, EN 60754-1 & 2.

RR KABEL FR / FR-LSH / LSOH



Multistrand bright electrolytic annealed bare copper conductor, FR PVC/FR-LSH PVC/LSOH Insulated Unsheathed Single core round flexible Industrial Power Cables for working voltages upto and including 1100 Volts (HSN CODE : 8544)

RATE / 200 MTR					
Size (Sq.mm)	Configuration	AMPS	RR KABEL FR FR PVC INSULATION	RR KABEL FR-LSH FR-LSH PVC INSULATION	RR KABEL LSOH LSOH INSULATION
0.75	24/0.2	8	1855	1920	2168
1.0	32/0.2	13	2469	2549	2784
1.5	30/0.25	17	3612	3738	3965
2.5	50/0.25	24	5828	6044	6427
4.0	56/0.3	30	8893	9204	9711
6.0	84/0.3	38	13222	13652	14404

Note: As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guidelines and are as per market convention, It may vary within the prescribed limit of IS:8130-2013, with related classes and tables.